

# **ASP TM25-384**

# THERMAL IMAGING MONOCULAR



The Asp TM25-384 handheld observational thermal monocular is equipped with a 384×288 infrared detector and a 1024×768 OLED display. It supports functions of observation, hot spot tracking, distance measurement, Wi-Fi hotspot, and so on. The high-sensitivity built-in thermal detector provides you with clear view even in total darkness. The monocular is mainly applied to scenarios such as patrolling, law enforcement, searching and rescuing, drug enforcement, anti-smuggling, criminal seizing, hiking, travel, and hunting, etc.

- 384×288 resolution, high sensitivity detector
- Adaptive AGC, DDE, 3D DNR
- 1024×768 resolution 0.39-inch OLED display
- Built-in memory supports video recording/snapshot capturing
- Wi-Fi hotspot
- Built-in rechargeable Li-Ion battery
- Up to five hours continuous running (with Wi-Fi hotspot function off)
- Limited 3-year warranty

## **FUNCTIONS**

#### Distance Measurement:

The device realizes distance measurement function after marking the top and bottom of target, and input the target height.

### Hot Spot Mark:

The device detects and marks the hot spot of highest temperature.

#### Mode Switch:

Device supports pallet switch and distance measurement.

## Storage:

Built-in memory module supports video recording/snapshot capturing.

#### Digital Zoom:

Device supports 1x and 2x digital zoom.

## Wi-Fi Hotspot:

Device can capture snapshots, record videos, and set parameters via APP after being connected to your phone.







Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.

# **SPECIFICATIONS**

Detector Type	Vanadium Oxide Uncooled Focal Plane Arrays
Resolution	384 × 288
Refresh Rate	50 Hz
Detector Pitch	17μm
Response Wavelength	8µm to 14µm
NETD	< 35mk (@25°C, F#=1.0)
Lens Focal Length	25mm
Field of View	14.9° × 11.2°
F-number	1.0
Optical Magnification	1.7x
Digital Zoom	1x, 2x
FFC (Flat Field Correction)	Auto, Manual, External Correction
Palettes	Black hot, White hot, Red hot, Fusion
Monitor	0.39-inch, OLED, 1024 × 768
Hot Track	Yes
Storage	Built-in memory module (16GB)
Record Video	Support on-board video recording
Capture Snapshot	Yes
Wi-Fi	Yes, Hotspot
Battery	Built-in rechargeable Lithium battery
Battery Operating Time	Up to 5 hours continuous running
Battery Capacity Display	Yes
Power	5V DC/2A, 2W
Working Temperature	-30°C to 55°C (-22°F to 131°F)
Protection Level	IP67
Dimensions	189 × 74 × 66 mm (7.4 × 2.9 × 2.6 in)
Weight	460 g (16.2 oz)

Specifications are subject to change without notice.



MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | Andrey Lyapchev #7 | Sofia, P.C. 1756 | Bulgaria Tel. +44.292.255.0509 | info@agmglobalvision.eu | www.agmglobalvision.eu